




**LANDT INSTRUMENTS**

**CT2001A-5V1mA Battery Test System**

Model	CT2001A-	5	V	1	mA	Battery Test System				
Item		Value								
Input Power		AC 110V ±10% / 60Hz or AC 220V ±10% / 50Hz								
Working Power		30			W					
Resolution		AD : 16bit ; DA : 16bit								
Input Impedance		≥1MΩ								
Voltage	Test Range	Charge : 10mV~5V			Discharge : 10mV~5V					
	Lowest Discharge Voltage	10mV								
	Accuracy	± 0.1% of FS +0.1% RD								
	Stability	± 0.1% of FS +0.1% RD								
Current	Test Range	Charge : 0.005mA~1mA			Discharge : 0.005mA~1mA					
	Accuracy	± 0.1% of FS + 0.1% RD								
	Stability	± 0.1% of FS + 0.1% RD								
Power	Single Channel Power	3.75W								
	Stability	± 0.2% of FS + 0.1% RD								
Time	Current response	Current (10%~90% range) Response in 20ms								
	Step Duration	≤(365*24) hrs/Step			Timing Format (hh:mm:ss)					
Data Acquisition	Recording Condition	Δt: (60s~60000s)								
		Voltage ΔU : (20mV~5V)								
	Current ΔI : (0.002mA~1mA)									
Charge	Record Frequency	0.33Hz								
	Charge Mode	Constant Current (CC) Charge, Constant Voltage (CV) Charge, CC-CV Charge								
Discharge	Cut-off	Voltage, Current, time, Capacity, -ΔV								
	Discharge Mode	Constant Current Discharge, Constant Power Discharge								
Cycle	Cut-off	Voltage, Current, time, Capacity, -ΔV								
	Cycle numbers	1~65535								
	Steps in each cycle loop	63								
Protection	Safety Characteristic	Support 3 inner cycles								
		<ul style="list-style-type: none"> <li>• Data saved automatically at power failure</li> <li>• Top Voltage Cut, Bottom Voltage Cut, Top Current Cut, Bottom Current Cut, Time Cut</li> </ul>								
Channel Characteristic		Independent Voltage/Current Control and Supply								
Connection		4-Electrode, 2-Electrode								
Noise		<85dB								
Communication port		RS422								
Data export		EXCEL, TXT								
Channel Numbers		8								
Working Environment										
Item		Value								
Working Temperature		0 ~ 40°C								
Storage Temperature		-10 ~ 50°C								
Humidity		≤70% RH								
Storage Humidity		≤80% RH								

Item	Value	
Clamp		
Equipment Dimension(L*D*H) (in)	20*15*5	
Equipment Picture		

**Landt Instruments**

Croton-on-Hudson NY 10520  
 Phone: (888)505-1296  
 Email:landt@landtinst.com  
[www.landtinst.com](http://www.landtinst.com)