

LANDT INSTRUMENTS

CT2001A-5V5ABattery Test System

Model	CT2001A- 5 V 5000 mA	Battery Test System									
Item	Value										
Input Power	AC 110V ±10% / 60Hz or AC 220V ±10% / 50Hz										
Working Power	2800	W									
Resolution	AD : 16bit ; DA : 16bit										
Input Impedance	$\geq 1M\Omega$										
Voltage	Test Range	Charge : 10mV~5V	Discharge : 10mV~5V								
	Lowest Discharge Voltage	10mV									
	Accuracy	$\pm 0.1\%$ of FS +0.1% RD									
	Stability	$\pm 0.1\%$ of FS +0.1% RD									
Current	Test Range	Charge : 25mA~5000mA	Discharge : 25mA~5000mA								
	Accuracy	$\pm 0.1\%$ of FS + 0.1% RD									
	Stability	$\pm 0.1\%$ of FS + 0.1% RD									
Power	Single Channel Power	350W									
	Stability	$\pm 0.1\%$ of FS + 0.1% RD									
Time	Current response	Current (10%~90% range) Response in 20ms									
	Step Duration	$\leq (365 \times 24)$ hrs/Step	Timing Format (hh:mm:ss)								
Data Acquisition	Recording Condition	Δt : (60s~60000s)									
		Voltage ΔU : (20mV~5V)									
		Current ΔI : (10mA~5000mA)									
	Record Frequency	0.33Hz									
Charge	Charge Mode	Constant Current (CC) Charge, Constant Voltage (CV) Charge, CC-CV Charge									
	Cut-off	Voltage, Current, time, Capacity, $-\Delta V$									
Discharge	Discharge Mode	Constant Current Discharge, Constant Power Discharge									
	Cut-off	Voltage, Current, time, Capacity, $-\Delta V$									
Cycle	Cycle numbers	1~65535									
	Steps in each cycle loop	63									
	Cycle loops in a cycle	Support 3 inner cycles									
Protection	Safety Characteristic	<ul style="list-style-type: none"> • Data saved automatically at power failure • Top Voltage Cut, Bottom Voltage Cut, Top Current Cut, Bottom Current Cut, Time Cut 									
Channel Characteristic		Independent Voltage/Current Control and Supply									
Connection		4-Electrode, 2-Electrode									
Noise		<85dB									
Communication port		RS422									
Data export		EXCEL, TXT									
Channel Numbers		8									
Working Environment											
Item		Value									
Working Temperature		0 ~ 40°C									
Storage Temperature		-10 ~ 50°C									
Humidity		$\leq 70\%$ RH									
Storage Humidity		$\leq 80\%$ RH									

Item	Value
Clamp	
Equipment Dimension(L*D*H) (in)	20*15*5
Equipment Picture	

Landt Instruments

Croton-on-Hudson NY 10520

Phone: (888)505-1296

Email:landt@landtinst.com

www.landtinst.com